

Amphenol Sensors

Connecting your world through
Sensor Innovations

HVAC for Medical Facilities

Amphenol Sensors is a leading innovator in sensor technologies and measurement solutions. Offering the most diverse sensor portfolio of standard and customized products for the world's most demanding regulatory and industry-driven applications, Amphenol creates value by providing critical information for real-time decisions.

The demands of today's healthcare industry require not only the highest criteria in the direct care of a patient, but also the highest quality, accuracy and efficiency in those facilities that allow for that care.













Within a medical facility, the proper operation of its heating, ventilating and air conditioning (HVAC) systems also ensures proper operation of various medical support functions to provide for the health, comfort and safety of that facility's occupants, including patients, visitors, and staff.



















Amphenol Sensors' diverse portfolio of world class sensor solutions touches nearly every facet of a medical facility's HVAC systems to ensure not only the utmost in conditions for patient care and recovery, but also long-term efficiency to achieve green building status.



Amphenol Sensors

HVAC for Medical Facilities

Application		Solution	Technology & Features	
Carbon Dioxide (CO ₂)	Fresh Air Ventilation Control	<ul style="list-style-type: none"> Monitors patient/staff occupancy to ensure proper CO₂ levels For use in temporary medical facilities with no standard Building Automation System (BAS) in place 	<ul style="list-style-type: none"> Dual channel automatic calibration Outputs: 0-10 V, 0-5 V, 4-20 mA, relay, BACnet 	
	Oxygen	<ul style="list-style-type: none"> Aids patient breathing in ventilator equipment 	<ul style="list-style-type: none"> 0-100% volume oxygen Wide pressure range Realtime measurements Linear Low power electrochemical sensor 	
Humidity	Humidity Control	<ul style="list-style-type: none"> Prevents condensation that can cause mold growth, in addition to harmful respiratory conditions Ensures human comfort and energy efficiency 	<ul style="list-style-type: none"> Accuracy options: 2%, 3%, 5% Outputs: 0-10 V, 0-5 V, 4-20 mA Field replaceable Relative Humidity (RH) sensor 	
Dew Point	Absolute humidity control	<ul style="list-style-type: none"> Ensure human comfort and energy efficiency Prevent condensation 	<ul style="list-style-type: none"> Real-time measurements Digital outputs Custom package options 	
Gas Detection	Hospital Beds and Wheelchairs	<ul style="list-style-type: none"> Ensure human comfort Prevent skin infections 	<ul style="list-style-type: none"> Real-time measurements Digital outputs Custom package options 	
Pressure	Differential Pressure Measurement	<ul style="list-style-type: none"> Negative-pressure patient isolation room monitoring 	<ul style="list-style-type: none"> Outputs: 0-10 V, 0-5 V, 4-20 mA Range: 0-0.3" WC, T30 Range: 0-0.5" WC, T10, T20 Piezoresistive sensor Offsets: 0, 1/4, 1/2 span Units: In. WC, Pa, or mm H₂O Accuracy: ±1% of span 	 
		<ul style="list-style-type: none"> Negative/Positive pressure room monitoring Fan/filter monitoring Sensing components for ventilators, sleep apnea, and oxygen concentrators 	<ul style="list-style-type: none"> ±0.5" WC and above High volume Accuracy: ±1.5 % of span 	  
	Climate Control Systems	<ul style="list-style-type: none"> Measures coolant pressure in HVAC systems 	<ul style="list-style-type: none"> Stainless steel pressure sensing element, aluminum housing, RD-connector Pressure range: 0-10 to 0-100 bar Temperature range: -40°C to 125°C Outputs: LIN, PWM, analog voltage 	
	HVAC Refrigerant	<ul style="list-style-type: none"> Measures low and high pressures of HVAC refrigerant 	<ul style="list-style-type: none"> Stainless steel, media-isolated 3 psi – 7500 psi Gauge, sealed and absolute piezoresistive transducers Output options: 5V, 4-20 mA, 4.5 V Accuracy: 1% Variety of ports Harness accessories available 	

Application	Solution	Technology & Features
Combined Pressure & Temperature	<ul style="list-style-type: none"> Measures pressure and temperature of coolants in HVAC systems 	<ul style="list-style-type: none"> Compatible to all currently used coolants (R134a, R1234yf, R744) High temperature accuracy and fast response time Stainless steel pressure sensing element, aluminum or steel housing, RD-connector or MQS-connector Pressure range: 0–10 to 0–200 bar Temperature range: -40°C to 125°C Output: LIN 
Temperature	<ul style="list-style-type: none"> Monitors critical equipment for over-temperature conditions 	<ul style="list-style-type: none"> Sensing element isolated from tag Dielectric 750 V_{AC} Eyelets to fit M3/M4/M5 screw sizes; additional diameters available Suitable for surface temperature measurement  
	<ul style="list-style-type: none"> Provides temperature control for nearly every aspect of a medical facility, from maintaining the air temperature in an operating room to monitoring hot water temperature supplied to restroom sinks 	<ul style="list-style-type: none"> Configuration: pipe clip Designed for 250,000 thermal cycles between 25°C to 85°C Pipe diameter range: 13-30 mm (1/2-1-1/8 in)  
	<ul style="list-style-type: none"> Provides temperature control for nearly every aspect of a medical facility, from maintaining the air temperature in an operating room to monitoring hot water temperature supplied to restroom sinks 	<ul style="list-style-type: none"> Configuration: integrated pipe clip IP57 ingress protection rating AEC Q200 REV (D) - pending Sensing element: dielectric 750 V_{AC} Pipe diameter range: 15-18 mm (5/8-1 in) Self-adjusts to irregular pipe surfaces  
	<ul style="list-style-type: none"> Provides uniform temperature for in-floor heating 	<ul style="list-style-type: none"> Configuration: boiler probe Connector series: molex minifit Full range of TCO temperature ratings according to EN60691 Range of connectors available  
	<ul style="list-style-type: none"> Provides position feedback for respiratory devices, prosthesis, infusion pumps, and electrophoresis devices 	<ul style="list-style-type: none"> Configuration: cable probe IP66 Rating Long-term stability Good thermal response time  
	<ul style="list-style-type: none"> Provides uniform temperature for in-floor heating 	<ul style="list-style-type: none"> Various resistance values available Various lead lengths available  
	<ul style="list-style-type: none"> Directly measures object temperature for automatic adjustments 	<ul style="list-style-type: none"> Auto control of fan and blowing rate Long detection range (~5 M)  
Position	<ul style="list-style-type: none"> Provides position feedback for respiratory devices, prosthesis, infusion pumps, and electrophoresis devices 	<ul style="list-style-type: none"> Programmable measuring angle with built-in redundancy Truly contactless operation with no wear; maintenance free Immunity to dust, moisture, vibration and extreme temperatures 
	<ul style="list-style-type: none"> Provides rotary angle/position feedback for power beds and power wheelchairs 	<ul style="list-style-type: none"> Robust, compact, and low profile up to IP69K Protection Absolute position feedback; position is not lost even on power loss High resolution up to 14-bit 
	<ul style="list-style-type: none"> Provides linear and rotary position sensing for centrifugators, X-ray and imaging systems, ventilators, patient monitor equipment, and HVACR 	<ul style="list-style-type: none"> Low profile Long life Excellent resolution and linearity 

Amphenol Sensors



*Scan the QR code to
access our library of
resources*

www.amphenolsensors.com

**Amphenol
Sensors**

© 2024 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.

Other company names and product names used in this document are the registered trademarks of their respective owners.

AAS-BR-257D - 04/2024